



Gildemeister Clamping Collets

Code	Description	d	D	L	a	Thread (F)	Diameter max	Hex max
9013E	AS12	26.8	34.0	88.0	15°5'	M24X1.0 Left	12.0	10.0
9012E	AS16/20 GS/ GM20	34.0	42.0	90.0	16°	M30X1.0 Left	24.0	19.0
9017E	AS16/20 GS/ GM20 Mod. 25	38.0	45.5	90.0	16°	M34.5X0.75 Left	27.0	24.0
9023E	GM16	30.0	39.0	80.5	15°	AtcB 27.12x1,5 60	16.0	14.0
9045E	AS25	45.0	60.4	164.0	15°	M40X1.0 Left	25.0	22.0
9046E	GS25 Mod. 32	45.0	60.4	164.0	15°	M42X1.0 Left	26.0	22.0
9069E	AS32 GM32/35	53.0	69.4	139.0	15°	M48X1.5 Left	38.0	31.0
9115E	GM42	64.0	80.5	134.0	15°	M59X1.5 Left	45.0	40.0
9132E	AS48	70.0	90.4	167.5	15°	M65X1.5 Left	53.0	45.0
9178E	AS67	90.0	115.4	183.5	15°	M85X1.5 Left	67.0	55.0