



Schütte Clamping Collets

Code	Description	d	D	L	a	Thread (F)	Diameter max	Hex max
9015E	SF13	25.0	36.1	75.0	15° 10'	M22X1 Left	13.0	11.0
9007E	SE16/18	31.9	42.0	84.0	15°	M28X1 Left	19.0	17.0
90076H	SG18-AG20	32.0	41.8	84.0	15°	M28X1 Left	18.0	16.0
90078H	SG18-AG20	320.0	41.5	84.0	15°	M30X1 Left	23.0	19.0
9016E	SF20	32.0	41.5	84.0	15°	M30X1 Left	20.0	17.0
9039E	SD/SE25-AF26	46.0	60.3	120.0	15°	M40X1.5 Left	30.0	28.0
SEF0020	36PC	56.0	72.0	139.0	15°	M52X1.5 Left	36.0	31.0
9070E	SD/SF/AF32	53.0	69.3	136.5	15°	M47X1.5 Left	38.0	32.0
9112E	AD40-SF42	62.9	78.3	157.0	15°	M56X1.5 Left	49.0	41.0
9139E	AF51-SF51-SD50	75.0	97.8	187.0	15°	M68X1.5 Left	51.0	44.0
9179E	SF63	90.0	115.3	212.0	15°	M82X1.5 Left	63.0	55.0
9187E	SF67	89.9	115.4	180.0	15°	M85X1.5 Left	70.0	63.0
9210E	SF81	109.0	138.8	241.0	15°	M100X1.5 Left	80.0	73.0